






Data sheet

CONTOUR CHECK ROUND & EDGE

Dimensional measurement of round, rectangular, or hexagonal profiles and rebar

Characteristics

- Stable data capturing & processing for products up to 1200 °C
- Show deviations and errors occurring during the production process
- Slim housing, can be moved in and out of the production line on a rail
- Mechanically stress-free base plate carries sensors separated from the housing
- Thermal protection by airflow and air cooling
- Intuitive SMART CORE ADVANCED software for defect visualization and documentation

					
	CONTOUR CHECK ROUND 45	CONTOUR CHECK ROUND 90 & EDGE 90	CONTOUR CHECK ROUND 120/150 & EDGE 120/150	CONTOUR CHECK ROUND 180/230 & EDGE 180/230	CONTOUR CHECK ROUND 500 & EDGE 500
Measuring range [mm]	45	90	120/150	180/230	500
Accuracy (trueness) [mm]	±0.015	±0.020	±0.025/±0.030	±0.035/±0.045	±0.090
Repeatability (precision) [mm]	0.004	0.0045	0.005/0.008	0.010/0.012	0.025
Number of axes [pc]	2, 3, 4, 6	2, 3, 4, 6	2, 3, 4, 6	2, 3, 4, 6	2, 3, 4
Frame width [mm]	860	1240	1720	2250	2550
Frame height [mm]	940	1170	1685	2215	2515
Frame depth [mm]	81	253	253	253	253
Passline height [mm]	450	570	835	1100	1250
Frame weight [kg]	125	580	930	1500	1900
Positioning system (optional)	✓	✓	✓	✓	✓
Blower	✓	✓	✓	✓	✓
Air cooling unit (optional, dimensioning depends on ambient conditions)	✓	✓	✓	✓	✓
Pyrometer (optional)	✓	✓	✓	✓	✓

Standard

Server PC with evaluation SW and data archive & control cabinet
 Measuring rate: 800 Hz ■ Temperature and air flow monitoring in frame
 Software license for 2P round ■ Cable set ■ Calibration set ■ Blower ■ Set of hoses

Optional

Different options for control cabinet, control panel, and visualization devices ■ Software add-ons for different profiles
 Database extension ■ Cooling unit ■ Different positioning systems ■ Industrial PC-set
 Level 2 interface ■ iba interface ■ Multi-client application ■ Speed monitoring
 Software add-on for 3-roll technology ■ Software add-on for rebar measurement
 Different integrated pyrometer sets ■ Uninterruptible power supply ■ Big LED display or big monitor
 Air conditioning unit for cabinet ■ Measuring rate 1600 Hz or 2000 Hz

Measurable profiles***Detectable rolling defects*****6 axes CONTOUR CHECK ROUND****6 axes CONTOUR CHECK EDGE**

*Valid for 6 axes CONTOUR CHECK ROUND & EDGE.

For the full overview of our available systems, please see our CONTOUR CHECK brochure at www.lap-laser.com

LAP Measurement Technology GmbH


Zeppelinstr. 23

21337 Lüneburg

Germany

P +49 4131 95 11-95

E info@lap-laser.com



Availability of products, features, and services may vary depending on your location. LAP and LAP product names are trademarks of LAP GmbH Laser Applikationen and/or its affiliated companies and are protected in multiple countries worldwide. Names of other companies and products are used solely for identification purposes (e.g., to indicate compatibility) and may be protected trademarks of their respective owners. Any use by third parties may infringe the rights of the respective trademark owners.

www.lap-laser.com/roundedge